




- 다양한 위치에 설치 가능
- 고강도 유지 나사
- 고강도 나사로 강력한 체결력
- Knob : Aluminium, Natural or Black Anodizing
- Bushing : Aluminium, Natural
- Spring, Screw : Stainless Steel, Passivated

1/4-20 Thread Size


Surface Styles




Part Name & Dimension



Unfastened



Fastened



Head Styles






Plate Hole Size



Ass'y



Part Numbers

Plate - Thickness (T)		1.0			1.5			2.0			2.7		
Plate Hole Length (R)		0.5			0.7			1.0			1.5		
Screw Size		20.0	22.0	24.0	20.0	22.0	24.0	20.0	22.0	24.0	22.0	24.0	26.0
Screw 돌출높이 (P1)		0.5	2.5	4.5	0.5	2.5	4.5	0.5	2.5	4.5	2.5	4.5	6.5
Screw 돌출높이 (P2)		7.5	9.5	11.5	7.5	9.5	11.5	7.5	9.5	11.5	9.5	11.5	13.5
Part Number	Slotted	Natural	U140-10S1N-20; U140-10S1N-22; U140-10S1N-24	U140-15S1N-20; U140-15S1N-22; U140-15S1N-24	U140-20S1N-20; U140-20S1N-22; U140-20S1N-24	U140-27S1N-22; U140-27S1N-24; U140-27S1N-26							
		Black	U140-10S1B-20; U140-10S1B-22; U140-10S1B-24	U140-15S1B-20; U140-15S1B-22; U140-15S1B-24	U140-20S1B-20; U140-20S1B-22; U140-20S1B-24	U140-27S1B-22; U140-27S1B-24; U140-27S1B-26							
	Phillips	Natural	U140-10S2N-20; U140-10S2N-22; U140-10S2N-24	U140-15S2N-20; U140-15S2N-22; U140-15S2N-24	U140-20S2N-20; U140-20S2N-22; U140-20S2N-24	U140-27S2N-22; U140-27S2N-24; U140-27S2N-26							
		Black	U140-10S2B-20; U140-10S2B-22; U140-10S2B-24	U140-15S2B-20; U140-15S2B-22; U140-15S2B-24	U140-20S2B-20; U140-20S2B-22; U140-20S2B-24	U140-27S2B-22; U140-27S2B-24; U140-27S2B-26							